

AquaGen

Technical Specifications



| | |
|-------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  Product Part Number | PV-X201 |
|  Installation Environment | Indoor, wash down, corrosive gases possible |
|  Voltage Supply | 120/208-230 VAC, 12.6 / 6.4A, 60Hz; 1-Phase GFCI |
|  Material | Stainless Steel, 316L |
|  Degree of Protection | NEMA 4 |
|  Operating Temperature | 32-104°F [0-40°C] |
|  Ambient Temperature | 90°F (38°C) |
|  Dimensions (HxWxD) | AquaGen unit: 16.13" x 27.90" x 10.47"* Concentrator unit: 26.8" x 10.5" x 22.6" |
|  Weight | 85 lbs. / 38.5 kg (Dry), 95 lbs. / 44 kg (Wet) |
|  Approvals | UL, NSF CCS-14530 |
|  Gas Type | Oxygen only |
|  Plumbing | 2 inch |
|  Product Output | Maximum inlet pressure of 10 psi and an ideal flow rate of 45-65 GPM. Maximum working pressure: 50psi, 8 LPM @ 20 psi, 8.78 lbs./day pool, 7.91 lbs./day spa |

*Full product width is 27.90". Width of product casing minus flange inlet/outlet is 23.50".